```
2006 Zephyr
```

2006 Zephyr	1	
	Engine	• Cummins ISM, fully electronic, 10.8L diesel w/
	• Engine:	"VG" turbocharger & cooled ERG
< SPARTAN>	Peak Horsepower:	• 500 hp @ 1,900-2,000 rpm
	<ul> <li>Peak Torque:</li> </ul>	• 1550 lbft. @ 1,300 rpm
	Transmission	1
	Transmission:	• Allison MH-4000 electronic six speed w/two
		overdrives, push button control
Spartan Chassis, Inc.	Gear Ratios:	• $\frac{1^{\text{st}}}{2} \frac{2^{\text{nd}}}{2} \frac{3^{\text{rd}}}{4} \frac{4^{\text{th}}}{4} \frac{5^{\text{th}}}{2} \frac{6^{\text{th}}}{4} \frac{8^{\text{ct}}}{4} \frac{8^{\text{ct}}}{4}$
1165 Reynolds Rd		3.51 1.91 1.43 1.00 0.74 0.64 -4.80
Charlotte, Michigan 48813	Wheel Base	• 316 Inch (283" from frt. axle to drive axle)
(517) 543-6400 Fax (517) 543-7728	Wheel Base:     East Over Hence	<ul> <li>72.63 Inch</li> </ul>
	<ul><li>Font Over Hang:</li><li>Rear Over Hang:</li></ul>	• 128.25 Inch
Proudly Presents the New	Front Axle	
2006 K2 Chassis Custom	• Front Axle:	• Tuthill IFS1460 Independent Front Suspension
Built for:	<ul><li>Capacity:</li></ul>	• 14,600 lb.
	<ul><li>Capacity.</li><li>Track</li></ul>	• 85.10" track width w/ oil bath
	Rear Axle	
(Tiffin Motorhomes, Inc.	• Drive Axle:	• Meritor RC-23-161 w/73.40" track width, oil bath
		bearings and hub piloted wheel ends.
	• Ratio:	• 4.30:1 "Quiet-Gear" for RV's
~ 2006 Zephyr ~	• Tag Axle:	• 10,000 lb. maximum capacity
	Brakes	
	Front and Rear Service:	• Full air brakes w/automatic slack adjusters
		16.5" x 5.0" front, & 16.5" x 7.0" rear
	• Engine Brake:	• 2 Stage "JAKE" engine compression brake
New Cummins 10.8 liter 500HP	ABS Brakes:	WABCO 4M/4S ABS system
ISM Electronic Diesel Engine	<b>Cooling System</b>	$1.470 in^2 AKC = 11.1 in 0 - 11.1$
• 14.6 IFS w/55 degrees of wheel cut	• Side mounted radiator:	• 1,478 in <sup>2</sup> AKG parallel airflow system with low profile radiator, charge air cooler, and integrated
<ul> <li>Hadley SLS – Automatic</li> </ul>		A/C condenser utilizing a modulated belt driven
Electronic Air Leveling System		cooling fan.
Adjustable Foot Pedals	<b>Electrical System</b>	
• VIP "Smart-Wheel"	• Alternator:	• 270 amp. Leece-Neville alternator
Automatic Moisture Ejectors	• Batteries:	• (2) Douglas 950 cca batteries
• 270amp Alternator	Frama	
• 15,000 lb. Capacity Tow Hitch w/ Electrical Connector	<ul> <li>Frame</li> <li>Front Drop:</li> </ul>	• 10.25" x 3.50" x .38"
<ul> <li>3yr/50,000 Mile "No Deductible"</li> </ul>	<ul><li>Center Rail:</li></ul>	• 8.25" x 3.50" x .38"
Warranty	Rear Drop:	• 9.00" x 2.75" x .38"
	Fuel Tank	
Chassis Weight Ratings:	Tank Capacity:	• 150gal, dual fill w/ side mounted sending unit
• GVWR 44,600 lb.	Steering System	
• Front GAWR 14,600 lb.	• Steering Gear:	• ZF-8098
• Rear GAWR 20,000 lb.	• Steering Wheel:	• VIP wood grain leather wrapped "Smart-Wheel"
• Tag Axle 10,000 lb.	• Steering Cramp Angle:	<ul> <li>55 degree</li> <li>Douglas tilt &amp; tolosooping</li> </ul>
• GCWR 59,600 lb.	Steering Column:	Douglas tilt & telescoping
* Includes 24/7 "Roadside Companion"	Suspension	• Reyco 240AR Suspension w/ electronic air dump
program for duration of Warranty.	Suspension:     Shoele Abaseberg	<ul> <li>Reyco 240AK Suspension W electronic an dump</li> <li>Bilstein gas-pressurized hydraulic shocks</li> </ul>
	Shock Absorber:	Enstein Sus pressurized nyuruure shoeks
Spartan Motors, Inc. reserves the right to change	Tires/Wheels	• 295/80R22.5 XZA2 Michelin Tires
the above specifications without notifications. Revision: 1.2006	Tires:	
	Wheels	• (6) Accuride Aluminum & (2) Steel wheels
	• Wheels:	